



Recovery Equipment

Dave Bland Engineering would like to thank you for your recent interest in the supply and fitting to your chassis one **4000 KG slide and tilt body, fitted with a 2000 KG rear-mounted spec lift**. We have pleasure in enclosing your specification details as required.

Main Slide Body Design and Construction

4000 KG CAPACITY STEEL BODY

- ✓ This body capacity will depend on chassis type and overall GVW
- ✓ Body is generally built on chassis from 7tonnes to 10 tonnes

DIMENSIONS

- ✓ Body 22'
- ✓ Overall width of body can be constructed up to 2300mm

BEACON ARCH AND FRONT NUDGE BAR

ALL STEEL BODY

- ✓ With fully welded steel treadplate flooring
- ✓ Beacon flyer and front nudge bar
- ✓ Nylon wear strips between body and subframe
- ✓ Twin tilt body rams
- ✓ Double acting hydraulic cylinders with 70mm bores
- ✓ 12ft slide off ram

PLASTIC TOOL LOCKER

- ✓ 36"x20"x20" fitted to near-side of chassis (where possible)

BODY SIDE CAPPING

- ✓ Stainless steel capping fitted to protect body paintwork and is finished with an anti-slip safety tape

VEHICLE SECURING

- ✓ 12 deck mounted lashing tie down rings
- ✓ Set of 4 deluxe transporter tie down straps with soft restraining loops

90" WINCH BOBBINS

- ✓ Enables side winching for the recovery and loading of badly damaged vehicles

Spectacle Lift

2000 KG CAPACITY

- ✓ Gold zinc coated spectacle lift head
- ✓ Fitted with flip over head for easy stowage when not in use

- ✓ Spec beam is powered in and out with a manual safety lock in the open and closed position
- ✓ Twin double acting hydraulic cylinders with 70mm bores
- ✓ 1 pair of spectacle lift tie down ratchet straps
- ✓ 1 pair of wheel space reducing bars are fitted to enable the transport of vehicles with small diameter wheels
- ✓ 50mm tow ball

Hydraulic System

- ✓ Vehicle gearbox PTO will be fitted with a hydraulic pump
- ✓ Chassis mounted hydraulic tank with in-built cartridge filter

5 BANK SPOOL VALVE SET UP AS FOLLOWS

- ✓ Winch control with electro hydraulic control
- ✓ Slide body on/off
- ✓ Tip body up/down (inc. auto tilt)
- ✓ Spectacle lift up/down
- ✓ Spec beam in/out manual safety lock
- ✓ Fully enclosed stainless steel spool valve cover

8000 lb HYDRAULIC WINCH

- ✓ Fully compliant to new EN 14492-1 regulations
- ✓ With radio remote and manual override lever
- ✓ 3560kg line pull - Rated line pull of 34.9kN

Electrical

- ✓ Vision Alert LED Light bar
- ✓ 1 pair of upper flyer mounted work lamps
- ✓ 1 pair of lower flyer mounted work lamps
- ✓ 1 pair of flyer mounted stop/tail/indicator lamps
- ✓ Radio remote winch control
- ✓ Tow ball & 7 pin plug
- ✓ 24/12V dropper fitted to 7 pin plug

Finishing

- ✓ Primed and painted in 2 pack
- ✓ Under body wax-oiled

Type Approval

- ✓ Issuing of Vehicle Type Approval certification to comply with current EU legislation

SUPPLIED, PAINTED AND FITTED

£ 37,400.00 + VAT

Should you like more information, or if we can be of further assistance to you, please do not hesitate to contact us accordingly.

Assuring you of our best attention at all times,
Yours faithfully

Dave Bland

DAVID BLAND
Proprietor