

## Vehicle Summary XF 480 FAR 6X2 Podvozek HNJ na konci, akce RIG2024A3

<b>Cab version</b>	Day Cab
<b>Tyres fr1 or fr axles</b>	F1,315/80R22.5GO KMAXS2 156/150 L Steering CBA
<b>Tyres driven rear axle(s)</b>	R1,315/80R22.5GO KMAXD2 156/150 L Traction DCA
<b>Tyres driven re2 or trailing axle</b>	R2,315/80R22.5GO KMAXS2 156/150 L Steering CBA
<b>Spare tyre</b>	SP,315/80R22.5GO KMAXS2 156/150 L Steering CBA
<b>Rear axle ratio</b>	Rear axle ratio 2.47
<b>Retarder system</b>	MX Engine Brake
<b>Fuel tank(s)</b>	340 l alu fuel tank LH, height 620 mm
<b>Wheelbase / rear overhang</b>	Wheelbase 4.80 m / rear overhang 2.90 m
<b>Cab colour</b>	E1980WHTE
<b>Engine</b>	Engine MX-13, 355 kW/483 hp. Cab Badge: 480
<b>Drawbar/coupling related max GCM</b>	Drawbar/coupling related max GCM 80000 kg
<b>Application packages 1</b>	No application option
<b>Connected Services</b>	PACCAR Connect
<b>Audio and infotainment</b>	DAF Infotainment Luxury with Luxury speakers
<b>Front axle</b>	Front: 8.00 t, parabolic, 163N
<b>Rear axle group</b>	Rear: 19.50 t, air suspension, SR1344
<b>Supplier tyres</b>	Goodyear
<b>Exhaust emission</b>	Exhaust emission Euro 6
<b>Gearbox execution</b>	Automated gearbox, TraXon, 12 speeds
<b>Chassis component layout</b>	Standard component location
<b>Exhaust discharge position</b>	Exhaust pipe horizontal, low
<b>Type plate related drawbar or solo application</b>	Type plate related drawbar appl. up to max GCM
<b>Body type</b>	No ex works body type
<b>Chassis weight related gross vehicle mass GVM</b>	Chassis weight related technical GVM max 27000 kg
<b>Vehicle warranty</b>	Warranty Plus-Driveline-3 years-500K

### Detailed Specification XF 480 FAR 6X2 Podvozek HNJ na konci, akce RIG2024A3

---

#### CAB EXTERIOR

- **Luxurious Day Cab with unrivalled aerodynamics for fuel efficient driving and low CO2 emissions. The huge and deep frontscreen, curved at the sides combined with large side windows offer an unsurpassed direct view for the driver, to enhance road safety. Cab length: 2030 mm; cab width: 2500 mm. Number of cab entrance steps: 3.**
- **LED head and bumper mounted fog lights.**
- Bi-reflector LED head lights with impact-resistant Lexan lens.
- **Dashboard switch and wiring including connectors A229 and A230 for easy mounting of two LED work lamps on the cab rear wall. The two work lamps are supplied loose.**
- Central door lock system with exterior light check function. Includes 2 remote control units with integrated snake blade key with flip mechanism.
- **Chassis front execution: robust provides for a three-piece steel protruding bumper with integrated fog lights, a radiator protection plate, a steel front underrun protection and black grille strips.**
- **Front windscreen of a laminated, double layer safety glass with solar control foil. A transparent foil is applied between the layers to help keeping radiation and resulting heat of the sun outside the cab, thus providing more comfort for the driver.**
- **Additional, lower window in the co-driver's door.**
- **Double layer safety glass. A transparent solar control foil is applied between the layers to help keeping radiation and resulting heat of the sun outside the cab, thus providing more comfort to the driver.**
- **DAF Corner View is a camera system replacing the front view and kerb view mirror. The system consists of a thin corner-view camera, positioned just below the front screen at the co-driver side, and a display, mounted on the A-pillar inside the cab. The camera offers a wider field of view and improved vehicle aerodynamics.**
- Maintenance free 4-point mechanical cab suspension with integrated shock absorbers.
- Rigid first cab entrance step with anti-slip tread.
- Head light beam for right-hand traffic.
- LED day time running lights are integrated in the head light units. They are ON when the engine is running.
- Black door handle and door handle surround. The sleek cab side wall is executed in cab colour.
- Main mirror and wide angle mirror.
- Camera at the rear of the vehicle for rear view. Camera images will be shown on the additional display in the dashboard wing belonging to the DAF Infotainment System: Luxury, Luxury Plus or Exclusive.

#### COLOURS

- Cab colour: E1980WHITE

## SLTV Palfinger/KOV XF480 FAR

- Colour of lower cab step: Stone Grey.
- Colour of mirror covers: black.
- Chassis colour grey.
- Colour of head lamp panel: Crystal White.
- Colour of bumper: Crystal White.

### CAB INTERIOR

- **ECAS remote control with illuminated buttons for various functions including four memory buttons for pre-set chassis heights.**
- **Adjustable arm rests at both sides of the driver seat.**
- **Soft woven, fabric door covering.**
- Water-to-air 3.8 kW auxiliary cab heater with residual heat pump. Control panel with 7-day timer.
- **Steering wheel with leather finish.**
- **Air suspended driver seat - Super Air. High backed with adjustable shoulder support. Two-step seat heating and active seat ventilation. Upholstery Habsburg for the seat facing, Alcantara for the borders and Leather for the edges.**
- **Foldable cinema co-driver seat with table feature. The head rest can be tilted and used as table tray. Cover material seat: fabric.**
- **Refrigerator on the engine tunnel, accessible from the top.**
- **Cab climate control automatically controls cab temperature, blower, air distribution and air conditioning**
- **Accessory power supply on the dashboard: 2x 12V/5A and one USB-A connection in the small storage compartment in the centre console. Additionally 2x 24V/40A (application connector A144) to the roof console.**
- **Roof hatch with electric control.**
- Left-hand drive.
- Cab interior trim colour: Luxury consists of a light interior trim colour on roof and roof console. Door panels and the part below the dashboard are grey.
- Dashboard finish: Vision - The dashboard descends towards the front screen to create more direct view on the road. The centre part has a plane finish, which can be used for various purposes.
- Cab interior decoration: Hexagon. Accents will be in facet black.
- Cab wallcovering textile with sound absorbing inner lining.
- The driver seat is fixed to the cab floor.
- The co-driver seat is fixed to the cab floor.
- Seat belts black.
- Extractable dashboard table at the top of the centre console.
- Open storage compartment in the centre console.
- Curtains along the windscreen and the side windows. Includes curtains for optional side and rear windows, if specified.

## SLTV Palfinger/KOV XF480 FAR

- LED cab interior lighting, comprising a.o. two large LED light units in the cab ceiling with dimmable flood light to light the whole cab, dimmable red night driving light and a separate spot light for driver as well as co-driver.
- Pollen filter with activated carbon to eliminate traffic and engine blow-by gasses and odours. Effectiveness 85% for particles up to 0.5 micron and 98% for particles up to 10 micron.
- Roller blind at the driver side to protect against sunlight.
- Electric window openers.

### COMMUNICATION AND DRIVING MANAGEMENT

- **Digital (smart) tachograph VDO DTCO with Global Navigation Satellite System (GNSS) receiver and Dedicated short-range communications (DSRC) unit, compliant to EU Mobility package 1 as described in the EU tachograph regulations.**
- **Speed limiter setting for cruise control/accelerator pedal: 90 km/h.**
- **Standard antennas: AM/FM/DAB/DAB+ radio frequencies, 2x cellular for use by mobile phones, GNSS for location purposes. Extra: CB antenna.**
- Wiring and connectors near the Fuse and Relay Board, for easy installing of a universal FMS (Fleet Management System) system, to read information as defined in the truck manufacturers' FMS standard.
- 10 year subscription for PACCAR Connect. PACCAR Connect is an online fleet management system giving insight in relevant truck, driver and location information.
- DAF Infotainment System: Luxury - includes an additional 10.1 inch touch display and control buttons in the dashboard wing. FM/DAB/DAB+ radio is integrated in the system as well as streaming functionalities via USB and Bluetooth including phone capabilities. Supports Apple CarPlay and Android Auto projection on secondary display. The Luxury speaker system consists of five speakers: two bass speakers in the door panels (one in each door), two tweeters on the A-pillar and a full-range frequency speaker at the centre of the dashboard.
- ACC (Adaptive Cruise Control) with FCW (Forward Collision Warning) and AEBS-3 (AEBS: Advanced Emergency Braking System). With ACC a set distance to the traffic ahead can be maintained; safety systems FCW and AEBS assist in avoiding or mitigating the impact of an impending collision with various moving or stationary objects in front of the vehicle, like other road users or crossing pedestrians, by alerting the driver and activating the brakes if necessary.
- Driver Performance Assistant (DPA). Interactive programme to support the driver in achieving the most cost effective driving style. The DPA information is shown on the 5 inch full colour TFT display in the instrument panel.

### SAFETY AND SECURITY

- **Emergency hammer to enable exit from the vehicle in case of an emergency.**
- **Main switch on the chassis.**
- Speed limit recognition informs the driver of the maximum permitted speed, using map-based information and traffic sign recognition via a camera at the front of the vehicle.
- DAF drowsiness detection assesses the driver's alertness through vehicle systems analysis and warns the driver, when deemed necessary.
- Lane Departure Warning System to prevent inadvertent lane changes due to driver's fatigue or distraction and to form an effective driving aid in low visibility conditions.

## SLTV Palfinger/KOV XF480 FAR

- Electronic Vehicle Stability Control system (VSC) to enhance the active driving safety. Improved directional stability (understeer, oversteer jack-knifing) and additional roll-over safety.
- Acoustic reverse warning with override switch.
- Basic engine immobiliser.
- Drive-off Assist informs the driver of vulnerable road users in the front bumper area and, if applicable, warns the driver to prevent collision.
- Safety system that detects and informs the driver of a moving object near the co-driver's side of the vehicle. The system also supports the driver to prevent collisions with other road users when changing lane.
- Preparation for an alcohol interlock system, consisting of a standardised interface (connector) for breathalysers in vehicles.
- The vehicle supplied by DAF is compliant with UN Regulation R155 concerning cyber security management systems as well as UN Regulation R156 concerning software update management systems.

### SUSPENSION AND AXLES

- **Automatic control to lift the leading and/or trailing rear axle(s) when the axle load on the driven axle permits lifting. The system operates at a vehicle speed as of 4 km/h.**
- Parabolic front suspension, regular driving height conditions.
- **Axle load monitoring: calculation and display of the axle loads of the rigid and trailer (if the trailer is equipped with EBS and axle load sensing). The axle load of a leaf suspended front axle of the rigid will not be displayed.**
- Front axle type 163N, 100 mm vertical offset. Parabolic suspension with shock absorbers and stabilizer. Max. load 8.0 tonnes.
- Driven rear axle and non-driven single mounted trailing rear axle with electronically controlled air suspension, including shock absorbers and stabiliser. Driven rear axle type SR1344 with single reduction and 4 air bellows. Trailing axle with 2 air bellows. Max. group load: 19.5 tonnes.
- Trailing axle load 7.5 t.
- Axle load limiter 11.5 t.
- Lifting device for the trailing rear axle.

### WHEELS AND TYRES

- **Front axle(s): tyre size 315/80R22.5, wheel size 22.5 x 9.00.**
- **Driven rear axle(s): tyre size 315/80R22.5, wheel size 22.5 x 9.00.**
- **Spare: tyre size 315/80R22.5, wheel size 22.5 x 9.00.**
- **Front axle: tyre size 315/80R22.5, Goodyear type KMAXS2, load index 156/150, speed index L, application Steering - Regional. Tyre label: rolling resistance C - wet grip B - noise 71dB(A), Category A.**
- **Driven rear axle: tyre size 315/80R22.5, Goodyear type KMAXD2, load index 156/150, speed index L, application Traction - Regional. Tyre label: rolling resistance D - wet grip C - noise 72dB(A), Category A.**
- **Trailing axle: tyre size 315/80R22.5, Goodyear type KMAXS2, load index 156/150, speed index L, application Steering - Regional. Tyre label: rolling resistance C - wet grip B - noise 71dB(A), Category A.**

## SLTV Palfinger/KOV XF480 FAR

- **Spare wheel: tyre size 315/80R22.5, Goodyear type KMAXS2, load index 156/150, speed index L, application Steering - Regional. Tyre label: rolling resistance C - wet grip B - noise 71dB(A), Category A.**
- **Trailing axle, tyre size 315/80R22.5, wheel size 22.5 x 9.00.**
- Supplier Goodyear.
- Tyre pressure monitoring.
- Steel disc wheels, silvergrey.
- Wheel protection rings with open centre section, colour silver-grey (RAL 9006).

### DRIVELINE

- **Eco performance: the shift strategy control settings of a vehicle with Eco performance focus on fuel efficiency and driveability. The fuel efficient setting, which is automatically selected, can temporarily be switched off by pushing the Eco off button to increase the performance of the vehicle.**
- **Automated gearbox software optimised for off-road applications including Rock-free function. Selection switches on the dashboard for on-road or off-road driving as well as for the Rock-free function.**
- **Rear axle ratio 2.47.**
- **Engine MX-13, multi torque 6 cylinder diesel engine, 12.9 litres. Output 355 kW (483 hp) at 1600 rpm. Maximum torque 2500 Nm at 900-1125 rpm.**
- **Automated direct drive gearbox TraXon 12TX2210, ratio 16.69-1.00, 12 speeds.**
- **Driven rear axle with a mechanical differential lock.**
- Exhaust emission Euro 6.
- Engine idle shutdown, after idling 5 minutes.
- Automated gearbox, TraXon, 12 speeds.
- Manoeuvring mode for maximum control: if selected, the driveline is gradually engaged, proportionally to the operation of the accelerator pedal.
- Traction aid 13.0 t.
- The ASR (anti-slip regulation) system prevents the driven wheels from slipping when accelerating at driving off and helps the vehicle to remain stable on critical road surfaces.

### BRAKE SYSTEM

- **MX Engine Brake. Hydraulically operated compression brake assembly integrated in the valve rocker group. The MX Engine Brake works simultaneously with the exhaust brake, resulting in a high combined braking power available at low engine rpm.**
- Pneumatic park brake control.
- Twin cylinder air compressor with heated dryer and economy mode.
- Ventilated disc brakes front and rear. Dual circuit air system with electronic control (EBS). Engine driven, water cooled air compressor with automatic air heated dryer.

## CHASSIS

- **Spare wheel carrier right-hand side.**
- **340 litres aluminium fuel tank at the left-hand side, height 620 mm.**
- Rear light unit with bulbs. The rear lights are ON when the engine is running.
- EAS unit at the right-hand side of the chassis, horizontal battery box and 45 litres tank for AdBlue® at the left-hand side.
- **Wheelbase 4.80 m / rear overhang 2.90 m.**
- **Exhaust discharge to the right-hand side.**
- Side member height 260 mm, thickness 7.0 mm. Full length inner reinforcement.
- Standard location of chassis components.
- Horizontal exhaust discharge at the side of the DPF/SCR unit via a low exhaust diffuser.
- Air tanks steel.
- Fuel tank at the left-hand side of the chassis.
- Front underrun protection (FUP), according to EU directive 2000/40/EEC.
- Spray suppression in the mudguards, according to directive 91/226/EEC.
- Temporary rear light brackets.

## DRAWBAR AND TRAILER EQUIPMENT

- **Electric trailer connection 24V with 15-pin socket. An additional 7-pin socket is mounted to connect the EBS system of the (semi-)trailer.**
- **Drawbar cross member with Rockinger trailer coupling: D-value 200 kN, Dc-value 140 kN, V-value 90 kN, S-value 1000 kg.**
- Type plate related drawbar application, up to the maximum allowable GCM.
- Pneumatic trailer connection with palm type couplings.

## BODIES AND PREPARATIONS FOR BODYING

- **Hardwired body signals and warnings.**
- **Four application connectors (cab: A210 and A225; chassis: A218 and A219) for the purpose of a remote control for various tilting body functions on the chassis.**
- **Loose supply of a wiring loom with LED-type side marker lights.**
- **Body attachment BAM 1, with consoles type B.**
- **Application connector (A212), providing extra flexibility for body related functions by allowing default pinning to be altered via DAVIE.**
- **Additional power supply including power connector (A219) in the chassis.**
- **ECAS control to secure vehicle stability during PTO operation. ECAS control comprises both ECAS in bump position and ECAS freeze.**
- **Connector for hardwired engine speed control on the chassis (A222). Control functions for engine speed adjustment, programmed engine speed selection, application speed limiter and remote engine start/stop.**

## SLTV Palfinger/KOV XF480 FAR

- The option **Additional rear light wiring** provides a second rear light extension harness to enable mounting of a second set of rear lights at the rear of a vehicle.
- **Preparation for aftermarket switches**, providing an application connector in the chassis (A212) and a wiring loom between this application connector and the chassis module rear.
- **CAN J1939 functions** in application connector (chassis: A218; cab: A225).
- **Additional cab spare wiring** providing application connector chassis (option 06692), 4 additional wires in the roof console and 5 extra spare wires in the dashboard.
- Additional light connector in the chassis.
- Chassis frame prepared for standard applications.

### POWER TAKE-OFF (PTO)

- **First gearbox PTO type N../10c**, mounted below the gearbox countershaft. Gear ratio 40/27, direct pump drive.

### 24V POWER SUPPLY

- **Alternator 110 A, batteries 2x 210 Ah AGM.**
- **The Battery Energy Monitoring system** measures voltages, current and temperature and provides an indication of the state of charge. When battery power is critical a warning will be shown to prevent road side breakdown.

### GVM AND GCM

- **Drawbar/coupling related max. GCM 80.000 kg.**
- Chassis weight related technical GVM max. 27000 kg.
- Driveline related max GCM 50000 kg class 3.

### APPLICATION CONDITIONS

- **Cyclonic air intake high.**
- Application class 0 comprises Western-Europe excluding United Kingdom and Ireland.
- Standard noise level.
- Cab insulation suited for moderate climate conditions (weather patterns remain within reasonable limits).
- Maximum ambient temperature 38 degrees.
- On-engine heated fuel pre-filter with water separator.

### SERVICE AND MAINTENANCE

- **Warranty Plus - Driveline**, takes care of 1 year complete vehicle as supplied by the OEM (excl. real wear parts), 2nd and 3rd year driveline up to 500,000 km and 1st year breakdown.
- ITS service.
- Service interval standard.
- A number of parts used to manufacture a vehicle contain SVHCs (Substances of Very High Concern) as defined in the REACH legislation.



# SLTV Palfinger/KOV XF480 FAR

## VEHICLE DELIVERY

- Lifting jack.
- Standard toolkit consisting of a 750 mm control lever, a 30/32 mm wheel nut wrench, a 30 mm box wrench, an approximately 800 mm long torque pipe, a 24/27 mm open end spanner, a T20 and T30/T45 torx screw wrench and a towing coupling with pintle pin.
- Whole Vehicle Type Approval (WVTA) for European Union.
- Type plate standard.
- CoC document printed in English (EN) language.
- CO2 calculation is possible in TOPEC RTS.

## CUSTOMER NEEDS

## DEALER OPTIONS

- 1 ks Hasicího přístroje 2kg
- Provedení RI kontroly XF
- Mytí + čištění vozidla před předáním
- Provedení PDI kontroly XF
- 1 ks Vesty DAF
- Autolékárnička
- Láhev motor. oleje 5l 10W-30 (využít do 1. výměny)
- 2 ks Klínů velkých + držáky - XF (FA,FAR)
- Prohlídka před předáním vozidla XF
- PDI BOX se základní výbavou XF (Cinema seat - ANO)
- Transport
- Marketingové předměty k novému vozu XF
- Zaškolení řidiče při předání vozidla XF
- Kalibrace TG - VDO nové generace - DTP
- Kabel. svazek na CZ mýtnou jednotku(přímé zapoj.)
- Základní parametrování PTO
- Ofukovací pistolka s přípravou za sedadlem XF

